

Flexible kitchen and ventilation duct KF



Uses

KF is approved as a connection between kitchen fan/stove hood and kitchen flue, and also between ventilation unit and duct. Approved acc. to Swedish Type Approval No. 0835.

Design

PVC coated encapsulated bronze coated wire. The helix is fully embedded, making the inside smooth.

Colour: grey.

Standard length

6 meters.

Properties

The hose has good resistance to chemicals and humidity. It is lightweight and axially compressible.

KF complies with the following Swedish demands:

- Boverket's (the Building Institute's) regulations for construction (1:4, 5:231, 5:526, 5:5332).
- Regulations from Statute Book of Sweden (kap 8, 4§ - Technical features)
- Tightness class D acc. to EN 13180, 6:25, 6:255
- Fire class E or material difficult to ignite acc. to EN 13501-1 (EN ISO 11925-2)
- Max pressure +3 000 Pa

Temperature range

-30°C to +80°C.

Accessories

Hose clamp suitable for ventilation: SBF

For connection to kitchen fan: SKF clamp

Dimensions / Weight

Inner diameter Ø mm	Weight, 6 m g
82	0,8
102	1,0
127	1,1
152	1,2
160	1,3
203	1,7
254	2,4
318	3,3
406	4,2
508	5,2
630	7,6

When ordering, please state

Kitchen and ventilation duct

KF - 125

Product

Dimension

Flexible kitchen & ventilation duct

KF

Pressure drop diagram, straight ducts

