

SBF

Quick clamp



Uses

Each size of the SBF speed clamp fits several duct dimensions.

The clamp is quickly and easily mounted: the band is pulled through the traction device (lock) to the position where it is to be fixed. Fold the traction device back and use a screw-driver to fix the position. For indoor use.

Design

Band: 9 mm width, 0,6 mm thickness, AISI 430, with rounded edges.

Screw house: tempered galvanized steel, AISI 430.

Screw: zinc plated finish with dark olive finish.

Head with both slot and cross.

Screwing torque: 4 Nm recommended

Dimensions (mm)

60-110	60-165	60-325
60-135	60-215	60-525

Packing

100 clamps/carton.

When ordering, please state:

Art. No. SBF clamp 135

Product

Dimension (mm)

SBF band



Uses

The SBF band comes in a handy plastic container, which makes it easy to cut the band to desired length. Easy to handle, quick to mount!

1. Pull out the desired band length by counting the "intervals" marked on the band. See table showing dimensions on the black container!
2. Cut the band and fold it back approx. 2 cm.
3. Push the band through the traction device (lock), under the screw, tighten the screw with a screw driver to secure band. The clamp is now ready.

For indoor use.

Design

Band: 9 mm width, 0,6 mm thickness, AISI 430, with rounded edges.

Screw house: tempered galvanized steel, AISI 430.

Screw: zinc plated finish with dark olive finish.

Head with both slot and cross.

Screwing torque: 4 Nm recommended.

Packing

SBF band: length 30 m in a plastic case
(Art.No. 60023-030)

25 traction devices in a separate bag
(Art.No. 60024-025)

When ordering, please state:

Art. No. _____ SBF band

Product _____

Do not forget to order traction devices!



SKL

Band clamp



Uses

The SKL band clamp is suitable for hoses with smooth outside.

Design

Band: 12 mm width, 0,7 mm thickness, stainless steel, AISI 304, SS 2333, with rounded edges.

Screw house: nickel plated.

Screw: zinc plated. Slotted hexagon-head screw, 7 mm.

Screwing torque: 8 Nm recommended.

Dimensions (mm)

15-25	50-65	155-181
19-28	58-75	180-206
22-31	68-85	205-232
26-38	77-95	231-257
32-44	87-112	256-282
38-50	104-138	282-308
44-56	130-165	

Packing

24 - 165 mm	100 clamps/carton
181-257 mm	50 clamps/carton
283-308 mm	25 clamps/carton.

When ordering, please state:

Art. No. SKL clamp 112

Product _____

Dimension (mm) _____